



Acrylic Panel Flow Meters with Flow Adjustment Valve

FEATURES:

- Low installation costs with easy mounting
- Light weight
- Compact body
- Durable material

APPLICATIONS:

Ideal for medical equipment, gas analysers, pollution monitors, and many other uses where an accurate measure of flow is required.

SPECIFICATIONS:

Accuracy:

± 4% Full Scale

Temperature Range:

60°C Maximum

Materials:

Float: 316 St St

Guide Rod: 316 St St

Body: Clear Acrylic

Thread: Brass or Plastic

Max Overpressure:

6 bar

Thread:

1/8", 1/4", 3/8", 1/2", 3/4", 1"



Model		Flow Rate	Thread
FMV 03	Water	1-12 LPH	1/8" BSP
FMV 06	Water	2-25 LPH	1/4" BSP
		4-40 LPH	1/4" BSP
FMV 15	Water	2-20 LPM	1/2" BSP
FMV 20	Water	4-38 LPM	3/4" BSP
FMV 25	Water	5-35 LPM	1" BSP
		20-70 LPM	1" BSP
		30-100 LPM	1" BSP
FMVA 06	Air	0.2-2 LPM	1/4" BSP
		0.4-5 LPM	1/4" BSP
		3-35 LPM	1/4" BSP
FMVA 10	Air	0.2-2 LPM	3/8" BSP
FMVA 15	Air	0.6-6m3/Hr	1-2" BSP

Other flow rates and thread combinations available, please contact us for more information

Weight and dimensions available upon request